



# AristoMax™

## CONVERSION VARNISH

**Conversion varnishes offer maximum aesthetics, durability, application flexibility, and superior vertical hang.**

AristoMax topcoat is a high-end, water-white, non-yellowing formula specifically designed for interior wood surfaces that are exposed to heat, wear, and moisture. With an easy application, you can spray confidently on all types of cabinetry and furniture.

### MAXIMUM BEAUTY & DURABILITY



Durability



Superior  
Vertical Hang



Clarity



High-Build

### PERFECT FOR:

- ✓ Kitchen cabinetry
- ✓ Residential and commercial furniture
- ✓ Architectural millwork
- ✓ Store fixtures and displays
- ✓ High-solids applications
- ✓ Meets and exceeds all KCMA testing standards



## ARISTOMAX / WHITE CV

	Product Code	Sheen	Material VOC (g/L)	Weight (% Solids)	Volume (% Solids)	Pot Life (hr)	Spread (ft <sup>2</sup> /gal)
Opaque basecoats that extend the life of your topcoat. These products are formulated for use as stand-alone white pigmented systems or to be tinted with recommended colorants.	E29W9410+K	10	505.36	55.09	41.89	24	671.94
	E29W9420+K	20	507.72	54.73	41.62	24	667.60
	E29W9430+K	30	509.93	54.40	41.37	24	663.52
	E29W9440+K	40	510.56	54.30	41.29	24	662.36
	E29W9460+K	60	512.00	54.08	41.13	24	659.70
	E29W9490+K	90	512.81	53.96	41.04	24	658.21

## ARISTOMAX PLUS / HIGH-COVERAGE WHITE CV

	Product Code	Sheen	Material VOC (g/L)	Weight (% Solids)	Volume (% Solids)	Pot Life (hr)	Spread (ft <sup>2</sup> /gal)
Superior coverage and hang. Tintable topcoats featuring "higher-hide" and ensuring maximum durability for white and off-white colors.	E29W9610+K	10	483.12	61.22	44.45	24	712.94
	E29W9620+K	20	476.66	61.87	45.15	24	724.25
	E29W9630+K	30	490.06	60.33	43.63	24	699.90
	E29W9640+K	40	488.64	60.54	43.81	24	702.75
	E29W9660+K	60	490.65	60.29	43.58	24	699.04

## ARISTOMAX / CLEAR TINT BASES

	Product Code	Sheen	Material VOC (g/L)	Weight (% Solids)	Volume (% Solids)	Pot Life (hr)	Spread (ft <sup>2</sup> /gal)
Clear tint base for darker colors. This formula is designed for tinting mid to dark colors and enhancing the longevity of your finish.	E29C9110+K	10	519.81	48.82	40.19	24	644.71
	E29C9120+K	20	535.89	46.80	38.40	24	615.97
	E29C9130+K	30	519.56	48.55	40.20	24	644.81
	E29C9140+K	40	525.11	47.86	39.58	24	634.90

## ARISTOMAX / TOPCOATS

	Product Code	Sheen	Material VOC (g/L)	Weight (% Solids)	Volume (% Solids)	Pot Life (hr)	Spread (ft <sup>2</sup> /gal)
Maximize the look and protection. AristoMax topcoats offer superior resistance against moisture, chemicals, UV rays, abrasion, and general wear and tear. Available in a variety of options to achieve the perfect look without sacrificing durability.	E29C9905+K	5	537.51	44.73	35.61	8	571.18
	E29C9910+K	10	529.79	45.34	36.46	24	584.88
	E29C9920+K	20	532.27	44.84	36.17	24	580.11
	E29C9930+K	30	533.44	44.60	36.03	24	577.85
	E29C9940+K	40	534.97	44.28	35.84	24	574.90
	E29C9960+K	60	536.59	43.95	35.65	24	571.80
	E29C9990+K	90	538.26	43.60	35.45	24	568.59

## ARISTOMAX / PRIMERS

	Product Code	Color	Material VOC (g/L)	Weight (% Solids)	Volume (% Solids)	Pot Life (hr)	Spread (ft <sup>2</sup> /gal)
Fast-dry primers with great sand-ability, for a smooth, even surface and enhanced adhesion. High-solids formula available.	P69W00057+K	White	362.29	54.78	35.68	8	572.33
	P69W00050+K	HS White	461.18	64.19	46.23	8	741.57

## ARISTOMAX / SEALER

	Product Code	Material VOC (g/L)	Weight (% Solids)	Volume (% Solids)	Pot Life (hr)	Spread (ft <sup>2</sup> /gal)
With excellent sand-ability and sag resistance, AristoMax sealer is applied prior to topcoat in order to achieve a uniform appearance. This sealer minimizes wood grain raise and uneven topcoat absorption.	E29C9000+K	618.49	36.08	28.94	8	464.12

## ONE CATALYST TO SERVE THEM ALL.

### ARISTOMAX / CATALYST

AristoMax catalyst is compatible with all AristoMax products, helping to facilitate the curing and hardening process.	Product Code
	M59C0037



LEARN MORE

\*Available in singles, pails, and drums